



NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday, January 20, 2011** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:
<http://www.nsf.org/Certified/PwsComponents/Listings.asp?Company=1F250&Standard=061&>

NSF/ANSI STANDARD 61

Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#).

Enecon Corporation

6 Platinum Court
 Medford, NY 11763
 United States
 800-436-3266
 516-349-0022



Facility : Medford, NY

Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Coatings - Fittings CHEMCLAD® XC[1]	>= 6"	CLD 23	EPOXY

[1] Colors: Light gray, white
 Number of Coats: 2 - 4
 Maximum Field Use Dry Film Thickness (in mils): 24
 Maximum Thinner: None
 Recoat Cure Time and Temperature: 4 hours at 77°F
 Final Cure Time and Temperature: 4 days at 77°F
 Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Pump

CHEMCLAD® XC[1]

>= 4"

CLD 23

EPOXY

[1] Colors: Light gray, white
Number of Coats: 2 - 4
Maximum Field Use Dry Film Thickness (in mils): 24
Maximum Thinner: None
Recoat Cure Time and Temperature: 4 hours at 77°F
Final Cure Time and Temperature: 4 days at 77°F
Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Tank

CHEMCLAD® XC[1]

>= 500,000 gal.

CLD 23

EPOXY

[1] Colors: Light gray, white
Number of Coats: 2 - 4
Maximum Field Use Dry Film Thickness (in mils): 24
Maximum Thinner: None
Recoat Cure Time and Temperature: 4 hours at 77°F
Final Cure Time and Temperature: 4 days at 77°F
Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Valve

CHEMCLAD® XC[1]

>= 6"

CLD 23

EPOXY

[1] Colors: Light gray, white
Number of Coats: 2 - 4
Maximum Field Use Dry Film Thickness (in mils): 24
Maximum Thinner: None
Recoat Cure Time and Temperature: 4 hours at 77°F
Final Cure Time and Temperature: 4 days at 77°F
Special Comments: Mix ratio of A:B is 5:3 by weight.

Number of matching Manufacturers is 1

Number of matching Products is 4

Processing time was 0 seconds

- [Search Listings](#) |
- [News Room](#) |
- [About NSF](#) |
- [Careers](#) |
- [NSF Mark](#) |
- [Client Log-In](#)

- [Privacy Policy](#) |
- [Site Map](#) |
- [Request Info](#) |
- [Contact Us](#) |
- [Copyright © 2004 NSF International.](#)